Maine Dept. of Health & Human Services SUBSURFACE WASTEWATER DISPOSAL SYSTEM APPLICATION Division of Environmental Health, 11 SHS (207) 287-5672 FAX (207) 287-4172 PROPERTY LOCATION >> CAUTION: LPI APPROVAL REQUIRED << Town/City LAMOINE City, Town, or Plantation LAMOINE Street or Road Date Permit Issued 8,257/2 Fee \$250 Double Fee Charged () DOUGLAS HIGHWAY Subdivision, Lot# OWNER/APPLICANT INFORMATION Name (last, first, MI) Owner \$15,00 OFP SURCHARGE Owner Town HOLT CHARLES Applicant Mailing Address CLO JOHN HOLT The Subsurface Wastewater Disposal System shall not be installed until a of Permit is issued by the Local Plumbing Inspector. The Permit shall LAMOINE BEACH ROAD Owner authorize the owner or installer to install the disposal system in accordance □ Applicant with the application and the Maine Subsurface Wastewater Disposal Rules. LAMOINE, ME, 04605 NICK - 210-415-1251 Daytime Tel. # Municipal Tax Map # 3 Lot # 3 6 JOHN - 207-667-8733 CAUTION: INSPECTION REQUIRED OWNER OR APPLICANT STATEMENT I state and acknowledge that the information submitted is correct to the best of I have inspected the installation authorized above and found it to be in compliance my knowledge and understand that any falsification is reason for the with Subsurface Wastewater Disposal Rules Application. Department and/or Local Plumbing Inspector to deny a permit. (1st Date Approved) oln SHoft Au Charles N Signature of Owner or Applicant Local Plumbing Inspector Signature (2nd Date Approved) PERMIT INFORMATION TYPE OF APPLICATION THIS APPLICATION REQUIRES DISPOSAL SYSTEM COMPONENT(S) 1. No Rule Variance 1. First Time System Complete Non-engineered System 2. First Time System Variance 2. Replacement System 2. Primitive System (graywater & alt. toilet) Cl a. Local Plumbing Inspector Approval 3. Alternative Toilet, specify: Type Replaced: LI b. State & Local Plumbing Inspector Approval 4. Non-engineered Treatment Tank (only) 3. Replacement System Variance 5. Holding Tank, _____ gallons 6. Non-engineered Disposal Field (only) Year Installed: a. Local Plumbing Inspector Approval 3. Expanded System b. State & Local Plumbing Inspector Approval 7. Separated Laundry System a. Minor Expansion 4. Minimum Lot Size Variance 8. Complete Engineered System(2000 gpd or more) ■ b. Major Expansion 5. Seasonal Conversion Permit 9. Engineered Treatment Tank (only) 4. Experimental System ■ 10. Engineered Disposal Field (only) DISPOSAL SYSTEM TO SERVE 5. Seasonal Conversion ☐ 11. Pre-treatment, specify: _ SIZE OF PROPERTY 1. Single Family Dwelling Unit, No. of Bedrooms: 3 ■ 12. Miscellaneous components TO BE sq. ft. 2. Multiple Family Dwelling , No. of Units: 11± acres 3. Other (SPECIFY) FUTURE GUEST SHORELAND ZONING TANK SYSTEM Per No 1. Drilled Well 2. Dug Well 3. Private COTTAGE Current Use: ☐ Seasonal ☐ Year Round ☐ Undeveloped 4. Public 5. Other: DESIGN DETAILS (SYSTEM LAYOUT SHOWN ON PAGE 3) 360 gallons per day TREATMENT TANK **DISPOSAL FIELD TYPE & SIZE** GARBAGE DISPOSAL UNIT 1. Concrete ■ 1. Stone Bed ■ 2. Stone Trench BASED ON ■ 1. No □ 2. Yes □ 3. Maybe 1. Table 4A (dwelling unit(s) 2. Table 4C (other facilities) SHOW CALCULATIONS for other facilities a. Regular 3. Proprietary Device 40 TYPE If Yes or Maybe, specify one below: ■ b. Low Profile a. Multi-compartment Tank a. Cluster Array C c. Linear 2. Plastic 3 BEDROOM HOUSE! □ b. __ _____.Tanks in Series 3. Other: LIFT STATION 270 GPD C. Increase in Tank Capacity 4. Other. GUESTCOTTAGE, CAPACITY 1000 NOKITCHEN gallons d. Filter on Tank Outlet SIZE 1920 2 sq. ft. | lin. ft. 90 OPD 360 GPD SOIL DATA & DESIGN CLASS **EFFLUENT/EJECTOR PUMP** DISPOSAL FIELD SIZING 3. Section 4G (meter readings) ATTACH WATER METER DATA LATTITUDE AND LONGITUDE at Center of Disposal Area Lat. 44 d 29 m 99.9 s Lon. 68 d 20 m 55.5 s PROFILE CONDITION 1. Not Required 1. Medium -- 2.6 sq. ft./gpd 1 D 2. May be Required 2. Medium-Large -- 3.3 sq. ft./gpd at Observation Hole #_ Depth 12 " 3. Required □ 3. Large - 4.1 sq. ft./gpd Specify only for engineered systems Depth 4. Extra Large - 5.0 sq. ft./gpd OF MOST LIMITING SOIL FACTOR DOSE: gallons if g.p.s., state margin of error_ 30 11 SITE EVALUATOR STATEMENT 6-3-16 I certify that on (date) I completed a site evaluation on this property and state that the data reported are accurate and that the proposed system is in compliance with the State of Maine Subsurface Wastewater Disposal Rules (10-144A CMR 241). 6-7-16 319

Site Evaluator Signature

SE#

WILLIAM A. LaBELLE, JR.

Site Evaluator Name Printed


Telephone Number

E-mail Address

Note: Changes to or deviations from the design should be confirmed with the Site Evaluator.

Page 1 of 3 HHE-200 Rev. 08/2015

		EWATER DISPOSAL SYS	STEM APPLICATION	Division o (207) 2:	pt. of Health & Human Services of Environmental Health, 11 SHS 87-5672 FAX (207) 287-4172
	Town, City, Plantation LAMOLNE		Subdivision HIGHWAY	Owner or Appl CHARLE	
		SITE PLAN	Scale 1" = <u>60</u>	_Ft. SITE (Attach	LOCATION PLAN map from Maine Atlas Time System Variance) The System Variance
	¥	(SEE ATTACHED	SITE PLAN)		
=	SOIL PROFILE DESCRIPTION	N AND CLASSIFICATION (Location of Observati	on Holes Shown Ab	ove or on pg. 2A)
	Observation Hole #1 Part Par	Test Pit	Observation Hole 1/2_" Depth of orga Texture SILTY CLAY 10 LOAM TO	ion Slope Limiting Factors Figure Figure	Mottling K JIGH N T T T T T T T T T T T T
	Site Evaluator's Signatu	319	6-7-1	(a Pag	ge 2 of 3 E-200 Rev. 08/2015



Maine Dept. of Health & Human Services Division of Environmental Health, 11 SHS (207) 287-5872 FAX (207) 287-4172 SUBSURFACE WASTEWATER DISPOSAL SYSTEM APPLICATION Town, City, Plantation Street, Road, Subdivision Owner or Applicant Name LAMOINE DOUGLAS HIGHWAY CHARLES HOLT SCALE: 1" = 20 FT. SUBSURFACE WASTEWATER DISPOSAL PLAN ERP, TOP OF 4'GRADE GRADE STAKE, STAKE, TOP IS 30" FOR TIE ABOVE GROUND. 4"SOLID, TYPICAL 8-HOLE DISTRIBUTION BOX SET ON FIRM LEVEL OF EDGE 1311 BASE, PROTECT STONE FROM FREEZING. TIE ENDS 2" PRESSURE_ TOGETHER LINE, PROTECT 161+ 161± 1940 FROM FREEZING NOTE : SEE AND CRUSHING, 0 ALL NOTES 6) PAGE 24. APPROX. -EDGE OF FILLY 4"DIA, PERF PIPE - EDGE OF SAND PROPOSED 40 TYPE B43 GSF UNITS TH PLACED IN 5 ROWS OF 8 SEPARATED BY 12", FOUR CORNERS ARE STAKED OUT, PRIVY: ELEVATION REFERENCE POINT **FILL REQUIREMENTS** CONSTRUCTION ELEVATIONS SYSTEM: 30" MIN, -11" Depth of Backfill (Upslope) Finished Grade Elevation Location & Description ABOVE GROUND , TOP OF 40" Top of Distribution Pipe or Proprietary Device ___19" N/A Depth of Backfill (Downslope) _ 4' GRADE STAKE Reference Elevation Is: _0 Depths @ cross-section shown below or on X-sec. detail. Bottom of Disposal Field (GSF UNIT) -30" DISPOSAL AREA CROSS SECTION (SEE ATTACHED CROSS SECTION) 1. Tank(s) must be 8' minimum from building. 2. Grade surrounding area to divert surface water away from system. 3. Well to be 51' minimum from septic tank(s) and 100' minimum from disposal field. 4. All work done adjacent to wetlands and water bodies must be done in compliance with section 12 of the Subsurface Wastewater Disposal Rules. Erosion and sediment control measures must be in accordance with the March 2003 edition of the Maine DEP Handbook "Maine Erosion and Sediment Control BMPS" (DEPW0588). 5. Install septic tank(s) risers 18" in diameter "minimum" to within 6" of finished grade on inlet, cleanout and outlet covers (recommend extending risers to finish grade). Install risers to finish grade of appropriate size to allow pump removal on all in-tank pump chambers and separate pump tanks. 6, Protect lift stations and pump tanks from freezing. 7. Full basement below grade foundation, frost wall or columns must be 20' minimum from edge of disposal field and slab on grade must be 15' minimum from edge of disposal field. 6-7-16 Page 3 of 3 HHE-200 Rev. 08/2015 Site Evaluator's Signature

	DATE	S.E.#	WILLIAM A. LABELLE, JR.	WILLIAN	/
	6-7-16	319	7	Chic	
······································	ON: LAMOINE HOLT	OWNER: LOCATION:	-36"	BOTTOM OF GSF UNITS:	B01
	WITH SECTION 11 OF SAID RULES.		- 23"	TOP OF GSF UNITS:	101
	DISPOSAL RULES. INSTALLATION CONTRATOR MUST BE FAMILIAR WITH SAID RULES AND CONSTRUCT SYSTEM IN ELLI COMBILIANCE		-19" -11" HID.	FINISHED GRADE: TOP OF PIPE:	
دا نخاب کی سیستریسی	TO THE RULES AND PRACTICES SET FORTH IN THE MOST CURRENT VERSION OF THE STATE OF MAINE SUBSURFACE WASTEWATER	CLEAN COARSE SHARP SAND INTO TOP 4 INCHES OF ORIGINAL SOIL CREATE A TRANSITION ZONE, SEC. 11-B.	1	ELEVATIONS: ELEV. REF. PT. (ERP):	ELE
	2	THOROUGHLY MIX. DISK OR ROTO-TILL		FILL UNDER AND AROUND SYSTEM TO BE COARSE GRAVELLY SANDS. 6'' OF MEDIUM TO COARSE SAND.	87
1/	ار آر	MICT B	1 (BOL)	ORIGINAL GRADE	_
<u>, , , , , , , , , , , , , , , , , , , </u>	12"\\ 40"F)\\\		12.	4:1, (25% SLOPE). 30" F124	4:1
	3% NO GREATER THAN	3%	3%	FILL EXTENSIONS	5 Z
	NOT BLOCK	GEOIL	4" PERF	12" CLEAN FILL OVER SYSTEM, (MINIMUM).	_
	ELLY	FILL MATERIAL SHALL BE 8"-12" THICK OVER GSF UNITS AND SHALL BE GRAVELLY COARSE SAND TO THE STANDARDS IN SEC. 11-E IN THE SUBSURFACE RULES.		TOP 4" OF FILL TO BE A GOOD LOAM SOIL MIX TO ESTABLISH A GOOD VEGETATIVE COVER; SEED AND MULCH TO PREVENT EROSION, SEC.11-G.	10 5 4 5 1
	MIN.	A) 19	9: 3: 12: 3: MIN TYP. TYP.	MATER AMAY FROM SYSTEM.	
	TION	SEC.	GSF UNITS CROSS	SRADE UPSLOPE	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \